

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-018	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE March 1997		3. REPORT TYPE AND DATES COVERED
4. TITLE AND SUBTITLE Advanced Fuel Hydrocarbon Remediation National Test Location - Site Characterization and Analysis Penetrometer System			5. FUNDING NUMBERS	
6. AUTHOR(S) Jeff Heath and Ernie Lory				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESSE(S) Naval Facilities Engineering Service Center Port Hueneme, CA 93043-4370			8. PERFORMING ORGANIZATION REPORT NUMBER TDS-2016-ENV (Revised)	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESSES			10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) The site characterization and analysis penetrometer system (SCAPS) with laser induced fluorescence (LIF) sensors are being demonstrated as a quick field screening techniques to determine the physical and chemical characteristics of subsurface soil and contaminants at hazardous waste sites.				
14. SUBJECT TERMS Site characterization and analysis penetrometer system (SCAPS), laser induced fluorescence (LIF), optical multichannel analyzer, photo multiplier tube.			15. NUMBER OF PAGES 2	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT UL	

19970411 011



TechData Sheet

Naval Facilities Engineering Service Center
Port Hueneme, California 93043-4370



TDS-2016-ENV (Revised)

March 1997

Advanced Fuel Hydrocarbon Remediation National Test Location Site Characterization and Analysis Penetrometer System

*Naval Command, Control and Ocean Surveillance Center, San Diego, CA
and
PRC Environmental Management, Inc., San Diego, CA*

The site characterization and analysis penetrometer system (SCAPS) with laser induced fluorescence (LIF) sensors (see Figure 1) is being demonstrated as a quick field screening technique to determine the physical and chemical characteristics of subsurface soil and contaminants at hazardous waste sites.

SCAPS is a collaborative development effort of the Navy, Army, and Air Force under the Tri-Service SCAPS Program. The current SCAPS configuration is designed to quickly and cost effectively distinguish areas contaminated with petroleum products (hydrocarbons) from unaffected areas.

Purpose of SCAPS at Port Hueneme

The SCAPS project at the Construction Battalion Center (CBC) at Port Hueneme is to obtain acceptance of SCAPS Laser Induced Fluorescence Technology by environmental regulators and develop a SCAPS field screening method. The SCAPS technology will also be evaluated for its: reliability, ruggedness, cost, and range of usefulness; specific data quality objectives; and easy operation.

Advantages

A SCAPS using LIF can define the boundaries of a hydrocarbon plume. With the boundaries defined, data analysis can be performed to indicate the least number of monitoring wells required for long-term plume movement and contaminants breakdown measurements. Investigation and remediation decisions can be made efficiently and effectively on site. This capability reduces the number of samples that need to be submitted to a laboratory for costly confirmatory analysis.

Technical Description

SCAPS LIF sensor technology will be demonstrated as a field screening technique for real time in place subsurface field detection and



Figure 1. SCAPS with LIF sensors.

identification of petroleum, oil, and lubricant hydrocarbons. An entire group of sensors is planned for eventual deployment using the SCAPS delivery platform. The SCAPS and its family of sensors will provide rapid, in place, subsurface measurements of many different contaminants and soil.

SCAPS is a suite of equipment mounted on a specially engineered 6 by 6 truck (60,000-pound weight class) designed for operations at hazardous waste sites (see Figure 2). The truck van contains a room for data collection and a room for hydraulic controls and penetrometer equipment. The heart of SCAPS is the sensors. These special sensors are designed to detect petroleum products and to determine soil characteristics. The hydraulic penetrometer thrust system pushes the penetrometer rod into the soil at a rate of 3 feet per minute. The penetrometer tip is equipped with sensors that can determine the physical characteristics of the soil as the rod is pushed through the soil. The tip has strain gauges that yield compression and push rod friction data. These data are used in a classification scheme to identify the types of soil and different layers encountered by the push rod probe.

One configuration to be demonstrated is a monochromatic (single light wavelength) LIF sensor and support system that is currently used in the Army and Navy SCAPS units. The second configuration, which is Air Force developed, uses a tunable (selective light wavelength) dye laser-equipped induced fluorescence system, called the **rapid optical screening tool** (ROST). Both systems deliver laser energy and ultraviolet light to the soil through a sapphire window near the probe's tip. The

laser energy excites the contaminant molecules, thus generating light (fluoresce) at different wave lengths. The resulting contaminant fluorescent energy passes back through the window and travels through a second fiber optic cable to the surface for collection and analysis. SCAPS employs an **optical multichannel analyzer** for signal detection processing and display. The fluorescent response measurement is directly related to concentration of the petroleum contaminant in the soil. ROST uses a **photo multiplier tube** approach in which a selected light wavelength can be used to cause contaminants to fluoresce. Thus identification of specific petroleum compounds is possible.

The demonstration is designed to highlight the LIF SCAPS and ROST technology as a field screening method by comparing real-time in place data to data produced by conventional sampling and analytical methods. For the purposes of the demonstration, conventional sampling and analysis will consist of taking soil samples from along the edge of SCAPS's push holes. Portions of the samples will be submitted to an analytical laboratory to support verification of the LIF SCAPS and ROST capability to characterize subsurface geology and soil parameters.



Figure 2. SCAPS truck van.

If you are interested in more information about SCAPS, contact:

Mr. Jeff Heath

Manager, Technology Application Branch
(805) 982-1657, DSN: 551-1657,
Internet: jheath@nfesc.navy.mil

or

Mr. Ernie Lory

Manager, Advanced Fuel Hydrocarbon Remediation
National Test Location
(805) 982-1299, DSN: 551-1299,
Internet: elory@nfesc.navy.mil

*Our Web address is: <http://www.nfesc.navy.mil>
For technical assistance, call: 1-888-4 THE ESC
(1-888-484-3372)*